

## 2.8 Wagon

**FAT TRUCK**<sup>®</sup>  
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



**Zeal Motor Inc.**

101, rue de la Production  
Cowansville, Quebec, Canada J2K 5H5

579.319.0060

[sales@zealmotor.com](mailto:sales@zealmotor.com)

[WWW.FATTRUCK.COM](http://WWW.FATTRUCK.COM)

# 2.8 Wagon

## SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS	
Payload	2200 lb (1000 kg)	Make	Hatz	Front & Rear	FAT TRUCK® LGP 1640 x 640 x 610	Front winch	
Passengers capacity	8 (2 front + 6 rear)	Model	1.95L Turbo diesel	Pressure	0.5 to 4.5 PSI (0.07 to 0.31BAR)	Additional battery	
Maximum speed on land	25 mph (40 km/h)	Emission standards	EPA Tier 4 Final EU Stage V	Pressure control	Automatic pressure control	Rear Hitch	
Maximum speed on water	3.1 mph (5 km/h)	Number of cylinders	4 cylinders	<b>FUEL SYSTEM</b>		Front and rear D-rings	
Maximum uphill & downhill	35°/ 70%	Displacement	119 po <sup>3</sup> (1.95 L)	Capacity	21 US Gal (80 L)	Studs for ice	
Maximum sidehill	22°/ 40%	Horsepower @ 2300 RPM	74 hp (55 kW)	Average fuel autonomy	12 h	Engine & hydraulic heater 110 V	
Turning radius	0°	Torque @ 1600 RPM	180 lb-ft (244 N-m)	<b>STANDARD EQUIPMENT</b>		Heater / defroster	
Shipping weight	5440 lb (2443 kg)	Cooling System	Liquid cooled	Doors	Lockable	Custom color	
Ground pressure fully loaded	1.6 lb/po <sup>2</sup> (0.11 kg/cm <sup>2</sup> )	<b>ELECTRICAL</b>		Operator seats	2 front seats with 3-points seat belts	Roof rack	
<b>SAFETY FEATURES</b>		Voltage	12 V	Lights	Front, brakes, position, flashers, dome	Exterior mirrors	
ROPS	ISO 3471	Alternator capacity	275 A	Horn	Electric	Back up camera	
EPA	Stage V	Battery capacity	960 CCA	Ingress	Front ladder with grab handles	Rear ROPS	
Brakes	Automatic safety brake	Battery type	AGM	Standard color	Red or white	Rear seats with safety belts	
<b>DIMENSIONS</b>		<b>TRANSMISSION</b>		Fire extinguisher	2.5 lb ABC	Directional light with remote control	
Height	101 in (2565 mm)	Type	Hydrostatic	4 sliding side windows		Front, side and rear light LED bar	
Length	146.5 in (3720 mm)	Final drive	Carbon fiber synchronous belts	Bilge pump		Extra heater	
Width	100 in (2540 mm)	<b>BRAKES</b>		Cup holders		4 corner LED beacon lights	
Ground clearance	20.7 in (526 mm)	Brakes	Positive deceleration through hydrostatic transmission	First aid kit		Electronic inclinometer	
<b>CONTROLS</b>		Parking brakes	Brake disc applied pressure released	Front and rear bumpers		Hydraulic capstan and accessories	
Controller	Microprocessor	<b>WARRANTY</b>		Lockable fuel cap		Cold weather package	
Steering	Joystick	Limited 1 year / 1000 hours (Which ever comes first)		Operator & Maintenance manual		Ventilation fan	
Display	Color display					Tow package	
						Wheel Pods™	
						Transportation trailer	
						Transportation rack	
						Amphibious trailer	
						Air conditioning	
						Back-up alarm	
						Variable cooling fan for engine	
						4-way camera system	
						Hot sticks storage tubes	
						Blanket over engine compartment	
						Roof Hatch	
						Bluetooth radio	

